



## KP 950 F

## TECHNICAL DATA SHEET

### Introduction

- > Strong stock removal with very high stability paper backing.
- > Fast grinding due to optimized zirconium oxide grain.
- > Excellent and uniform finishing due to precisely coating side.



Backing Material	Antistatic "F" weight paper
Bonding	Double resin
Mineral Type	Zirconium Oxide
Coating State	Closed coat
Manufacturing Width	1400mm

### Available Grits

24	36	40	50	60	80	100	120	150	180	220	240
		●	△	●	●	●	●	●	●	●	
280	320	360	400	500	600	800	1000	1200	1500	2000	2500

◀ Rough (Grinding)

Finishing (Polishing) ▶

- Introductory Remarks ● : Standard Grit △ : Non Standard Grit (Available under request with a MOQ)

### Application

- > Dry use
- > Rough sanding and fine sanding
- > Suitable for metal, stainless steel and hard wood only

### Field

- > Metal
- > Wood

### Form

- > Rolls
- > Discs
- > Belts

### Usage



Head Office:

Via Delle Groane, 27/E 20024 Garbagnate M. -Mi- Italy

E-mail: [itas.it@itasabrasivi.com](mailto:itas.it@itasabrasivi.com)

Website: [www.itasabrasivi.com](http://www.itasabrasivi.com)

I.T.A.S. ABRASIVES CO., LTD.

Yunxin Avenue, Yungang Road,  
414009, Yueyang City, Hunan, China

Tel. +86 0730 3072778 / +86 0730 3072998

E-mail: [itas.cn@itasabrasivi.com](mailto:itas.cn@itasabrasivi.com)